

Microphone Cable SC-MICRO-STAGE; 2 x 0,14 mm²; PVC Ø 5,80 mm; blue

Art. No.: 200-0372

ANALOG

DIGITAL

OFC



General Data

Article number :	200-0372
Name :	SC-MICRO-STAGE
EAN :	4049371186346
Properties :	Digital 110 Ω AES / EBU
Properties :	OFC oxygen free copper
Properties :	Analog
Application area :	Installation
Application area :	Mobile outdoor / indoor
Application area :	Stage / live
Application :	Microphone Cable
Colour :	blue
BPVo-Euroclass :	Fca

Technical Data

Signal transmission :	symmetrical
Construction :	(2LI2Y0,14mm ²)DY
Jacket material :	PVC
Jacket Ø [mm] :	5,80
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	0,14
Inner conductor Ø (audio) [mm] :	0,42
AWG (audio) :	26
Shielding :	Copper spiral shielding with 0.10 mm indiv. strands
Shielding factor [%] :	95
Copper strands (audio) :	18
Copper strand Ø (audio) [mm] :	0,10
Conductor insulation material :	Foam / Skin-PE
Conductor insulation Ø [mm] :	1,20
Weight per 1 m [g] :	50
UV-resistant :	yes
Fire load per m [kWh] :	0,22
Style variant :	round
Packing :	500 m spool
Packing :	100 m spool
Temperature min. [°C] :	-25
Temperature max. [°C] :	70
Width [mm] :	5,8
Height [mm] :	5,8

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	48
---	----

Capac. cond./shield. per 1 m (audio) [pF] :	120
Surge impedance (audio) [Ω] :	110
Insulation resist. per 1 km [GΩ] :	1
Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	130
Shield. resistance per 1 km [Ω] :	30